ViewSonic® VX750 LCD Monitor

17" MULTIMEDIA DESIGN DISPLAY

A design statement delivering excellent performance

The 17" LCD monitor VX750 is the first choice for all those who are looking for a stunning combination of **AESTHETICS, STYLE AND SUPERIOR PERFORMANCE**. Framed by a silver-metallic bezel, the panel delivers high contrast and brightness plus wide viewing angles to ensure a super-sharp picture from almost every perspective. The **RESPONSE TIME OF JUST 16 MILLI-SECONDS** further guarantees fast-moving Games, Video or DVD action is shown clearly. Two 5-watt speakers integrated in the side of the monitor provide the sound to accompany the images. In addition, this model comes with analogue as well as digital inputs to allow greater flexibility and connection options. Created for both business and home applications, the VX750 multimedia design LCD monitor represents the cutting edge in LCD technology.

OPTISYNC BEYOND DIGITAL Digital and analogue inputs expand connectivity options

Multi-mode input technology supports both digital (DVI) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.

Multimedia enhanced

Save desk and workspace and enjoy rich stereo sound with the built-in 5-watt stereo speakers & head phone jack.

ClearMotiv™ technology

Super-fast 16ms video response delivers broadcast-quality full motion video at 62.5 fps.

High brightness and contrast

270 nits (typ) brightness and a contrast ratio of 450:1 (typ) for rich, detailed images.

sRGB colour management

For a closer match of image display to print outs.

Full 17" viewable

OSD key lock and power lock

1 Watt power consumption in Active Off mode

Resolution of 1280x1024

OnView® controls for superior screen adjustability

Screen adjustments are precisely made via an easy-to-use on-screen menu.

VESA® 100mm wall mount compliant

PC and MAC® compatible

TCO'99 qualified

Design Statement

ViewSonic®
See the difference.™

ViewSonic® VX750 LCD Monitor

17" MULTIMEDIA DESIGN DISPLAY

specifications

17" MULTIMEDIA LCD MONITOR WITH ON-SCREEN MENU

LCD PANEL	**Type**	17" colour TFT active matrix SXGA LCD
	Display Area	33.8cm horizontal x 27.0cm vertical, 43.2cm diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	450:1 (typ)
	Viewing Angles	150° h, 125° v (at 10:1), 160° h, 145° v (at 5:1)
	Response Time	16 ms (typ)
	Brightness	270 cd/m² (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	**Analogue**	RGB analogue (0.7 Vp-p, 75 ohms)
	Digital	DVI-D (TMDS, 100 ohms)
	Frequency	F_H: 30-82 kHz, F_V: 50-85 Hz
	Sync	H/V separated (TTL), composite, sync on green
COMPATIBILITY	**PC**	PC compatible from VGA to 1280x1024
	Macintosh®[1]	Power Mac™ (up to 1280x1024)
CONNECTOR	**Signal**	RGB (15-pin mini D-sub), DVI-D, detachable cable
	Audio input/output	3.5mm stereo connector (line-in)/(line-out)
	Headphones	3.5mm stereo connector
	Power	3-pin plug (IEC) to External brick, 12 volt DC to Head
AUDIO	**Speakers**	2 x 5 watts
	Amplifier	5 watts at 1kHz
POWER	**Voltage**	AC 100-240 V (50/60Hz), auto switch
	Consumption	50 watts (max.)
CONTROLS	**Physical**	Power (soft), 1, menu up, down, 2, (enter) input select, volume +/-
	OSD	Auto image adjust, contrast, brightness, input select, colour adjust (sRGB, 9300K, 6500K [default], 5400K, user RGB), information (mode, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
OPERATING CONDITIONS	**Temperature**	0°C to 40°C
	Humidity	10% to 90% (non-condensation)
DIMENSIONS (W x H X D in mm)		502 x 405 x 195 (with stand), 502 x 340 x 63 (without stand)
WEIGHT	**Net**	5.6 kg
REGULATIONS		TCO'99, TÜV/GS, TÜV/Ergo, ISO 13406-2 (class 2), TÜV S, CE UL, cUL, IC-B, CB-Report, FCC-B, CB, CE, EPA, NOM, NEMKO, SEMKO, DEMKO, FIMKO, GOST-R, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, ENERGY, EnergyStar, PCT (BZ02), Taiwan green mark
POWER MANAGEMENT		TCO'99, ENERGY Standards
WARRANTY		Please see: http://www.viewsoniceurope.com/UK/Support/warranty.htm

ISO 9001 FM 40187

ISO 14001 EMS 40968

ViewSonic Corporation's QMS\EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

ViewSonic®
See the difference.™

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux Tel: +32 056/85 26 27
ViewSonic Denmark Tel: +45 70 22 11 71
ViewSonic Finland Tel: +358 (9) 54 06 40 70
ViewSonic Italy Tel: +39 0289 079 340
ViewSonic MEA Tel: +971 (0) 4 88 11 871
ViewSonic Norway Tel: +47 (0) 22 88 17 60
ViewSonic Spain Tel: +34 (0) 91 63 05 339
ViewSonic Sweden Tel: +46 (0) 8 50 71 30 00

[1] May require optional Mac adapter.

Copyright © 2004, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VX750-04/04-UK.

For more product information, visit us on the web at www.ViewSonicEurope.com